

The DESCHAMPS RANGE

GRP poles (glass reinforced polyester)

Tradition



Alizé



Aluminium poles

Pavoisement




Signs



Pennants



Flags



Hollow bodies

Windmill



Level crossing



Recommended dimensions for concrete bulks :

| | |
|--------------------------|------------------|
| 6 to 8 meters high poles | 60 x 60 x 80 cm |
| 10 meters high poles | 60 x 60 x 100 cm |
| 12 meters high poles | 80 x 80 x 100 cm |

| Standard equipment : ■ that can be replaced by an OPTION | TRADITION RANGE | | | | ALIZÉ RANGE | | |
|--|-----------------|----------------|--------------|-------------|-----------------|----------------|-------------|
| | WITHOUT BRACKET | | WITH BRACKET | | WITHOUT BRACKET | WITH BRACKET | |
| | Tête fixe | Tête tournante | Avec drisse | Sans drisse | Tête fixe | Tête tournante | Sans drisse |
| Standard shaft | | | | | ■ | ■ | ■ |
| Reinforced shaft | ■ | ■ | ■ | ■ | | | |
| Deschamps Finial | ■ | | | | | | |
| Plastic Finial | | ■ | | | ■ | ■ | |
| Deschamps finial with ball bearings | | OPTION | | | | | |
| Sliding GRP bracket with ball bearings | | | ■ | | | | |
| Cylindrical ALUMINIUM bracket with metal-plastic bearings | | | | ■ | | | ■ |
| Sliding ALUMINIUM bracket with metal-plastic bearings | | | | OPTION | | | OPTION |
| Sliding ALUMINIUM bracket with ball bearings | | | | OPTION | | | |
| Different Finials | OPTION | OPTION | | OPTION | OPTION | OPTION | OPTION |
| Intermediary rings | OPTION | OPTION | ■ | ■ | OPTION | OPTION | ■ |
| Weighted ring | | ■ | ■ | ■ | | ■ | ■ |
| External halyard | ■ | | | | ■ | | |
| Internal halyard | | ■ | ■ | | | ■ | |
| Fastening cleat | ■ | ■ | ■ | | ■ | | |
| Large Trapdoor | | ■ | ■ | | | | |
| Small trapdoor | | | | | | ■ | |
| Sheath + chocks, or | OPTION | OPTION | OPTION | OPTION | | | |
| Rocking base with | ■ | ■ | ■ | ■ | ■ | ■ | ■ |
| Cover for base | ■ | ■ | ■ | ■ | OPTION | OPTION | OPTION |